Power Hacksaws Air • Electric • Hydraulic

Cold cutting of large pipe up to 30" diameter and structural steel - on site

Ideal for a wide range of industries, including refineries, chemical plants, utilities, construction, offshore oil, mining, marine and demolition

- · Cold cutting of large pipe, structural steel, tanks, profiles and more
- Compact size for cutting in confined spaces



Model 5 1215 0070 Model 5 1220 0050 Model 5 1212 0050 **ELECTRIC HYDRAULIC** AIR ATEX Certified **Motor Specifications** Wt. Model No. **Throttle** (90 PSI) **Power** Strokes per Min. **Blade Stroke** Hose (lbs.) Pneumatic - 3/4" ID NPT Air Connection 100-350 23/8" 5 1212 0010 1.5 HP Roll Air Consumption: 51 CFM 1/2" 16.5 5 1212 0050 1.5 HP 100-350 23/8" Lever 1/2" 16.5 1.5 HP 23/8" 5 1212 0050A Lever II2GExhIIBT5Gb 100-350 1/2" 16.5 Electric - 11 Amps / 110 Volt (Also available as 220 Volt/50 Hz) 23/8" 5 1215 0070 1.5 HP 110V/60 Hz 16.5 Trigger 60-500 Cable

Oil Flow: 4 GPM at 2000 PSI

Assorted pipe clamps for pipes up to 30" OD or profile clamps for structural steel Manual or automatic feed

Hydraulic - 1/2" FF (HTMA) Couplings

Lever

3.8 HP

Heavy-duty saw blades from 8" to 37" long

5 1230 0050

HSS, HSS-SL, and carbidecoated blades available

Twist or lever throttle

Pneumatic, electric or hydraulic motor

100-500

Pneumatic: 3/4" NPT Connection Electric: 110 Volt (220V available) Hydraulic: 1/2" FF (HTMA) Couplings

Optional saw blade guide for added blade stability - ensures straight cutting!

Two sizes available (not required for operation)

Throttle Types for Pneumatic Saws:

1/2" ID

24.2

23/8"



Roll Throttle (air model 5 1212 0010) used only with automatic feed clamps

Lever Throttle (model 5 1212 0050) on/off for manual clamps

Model 5 1208 9980 Self-feeding Pipe Clamp

Hacksaw Clamps and Blade Guides

Metal carrying case available P/N 9 9910 0080

	Model No.	Cutting Diameter	Description
	5 1207 9910	2" to 6"	Pipe Clamp
	5 1202 9960	4" to 12 ³ / ₄ "*	Pipe Clamp
	5 1207 9970	Up to 13" OD	Blade Guide
	5 1207 8910	Up to 21" OD	Blade Guide
	5 1202 8970	21 ⁵ /8" x 11 ³ /8"	Profile Clamp
	5 1208 9980	Up to 12 ³ / ₄ "*	Automatic - Self-feeding Clamp (for pneumatic saws)
	5 1208 9990	Up to 12 ³ / ₄ "*	Automatic - Self-feeding (for electric and hydraulic saws)

Model 5 1202 9960 Pine Clamn for 4" to 123/4" dia.*





Model 5 1208 9990 Self-feeding Pipe Clamp for up to 12 3/4" dia. electric and hydraulic saws*



^{*} Cut up to 30" OD with two extension chains (order 2x P/N 5 1201 9030)

119

NEW! FAST CUT Hacksaw Blades

UP TO 60% FASTER THAN STANDARD BLADES!

Order No.	Length	Teeth/Inch	Thickness	Material	Max. Dia. of Cut
Z23-33 HSS	18"	6-8	5/64"	Cast Iron, Aluminum, Plastic	12 ³ / ₄ "
Z23-33 HSS-SL*	18"	6-8	5/64"	Cast Iron, Aluminum, Plastic	12 ³ / ₄ "
Z23-29 HSS	18"	8	5/64"	Cast Iron, Aluminum, Plastic	12 ³ / ₄ "
Z23-29 HSS-SL*	18"	8	5/64"	Cast Iron, Aluminum, Plastic	12 ³ / ₄ "
Z23-7 HSS	18"	14	5/64"	Steel	12 ³ / ₄ "
Z23-7 HSS-SL*	18"	14	5/64"	Stainless Steel	12 ³ / ₄ "
Z23-72 HSS	22"	6-8	5/64"	Cast Iron, Aluminum, Plastic	16³/4"
Z23-72 HSS-SL*	22"	6-8	5/64"	Cast Iron, Aluminum, Plastic	16³/4"
Z23-30 HSS	22"	8	5/64"	Cast Iron, Aluminum, Plastic	16 ³ / ₄ "
Z23-30 HSS-SL*	22"	8	5/64"	Cast Iron, Aluminum, Plastic	16 ³ / ₄ "
Z23-73 HSS	22"	14	5/64"	Steel	16³/4"
Z23-73 HSS-SL*	22"	14	5/64"	Stainless Steel	16³/4"
Z23-45 HSS	26"	6-8	5/64"	Cast Iron, Aluminum, Plastic	203/4"
Z23-45 HSS-SL*	26"	6-8	5/64"	Cast Iron, Aluminum, Plastic	203/4"
Z23-74 HSS	26"	8	5/64"	Cast Iron, Aluminum, Plastic	203/4"
Z23-74 HSS-SL*	26"	8	5/64"	Cast Iron, Aluminum, Plastic	203/4"
Z23-79 HSS	26"	14	5/64"	Steel	203/4"
Z23-79 HSS-SL*	26"	14	5/64"	Stainless Steel	203/4"
Z23-76 HSS	30"	6-8	5/64"	Cast Iron, Aluminum, Plastic	24 ³ / ₄ "
Z23-76 HSS-SL*	30"	6-8	5/64"	Cast Iron, Aluminum, Plastic	24 ³ / ₄ "
Z23-78 HSS	30"	8	5/64"	Cast Iron, Aluminum, Plastic	243/4"
Z23-78 HSS-SL*	30"	8	5/64"	Cast Iron, Aluminum, Plastic	24 ³ / ₄ "
Z23-75 HSS	30"	14	5/64"	Steel	243/4"
Z23-75 HSS-SL*	30"	14	5/64"	Stainless Steel	24 ³ / ₄ "
Z23-37 HSS	37"	14	5/64"	Steel	31 ³ /4"
Z23-37 HSS-SL*	37"	14	5/64"	Stainless Steel	31 ³ /4"

Heavy Duty Hacksaw Blades

Order No.	Length	Teeth/Inch	Thickness	Material	Max. Dia. of Cut
Z22-9 HSS	8"	8	1/16"	Steel/Aluminum	31/8"
Z22-10 HSS	8"	16	1/16"	Steel	31/8"
Z22-11 HSS	8"	24	1/16"	Sheet Metal	31/8"
Z22-6 HSS	12"	16	1/16"	Steel	6 ⁵ /8"
Z22-6 HSS-SL*	12"	16	1/16"	Stainless Steel	6 ⁵ /8"
Z22-31 HSS	12"	12	1/16"	Steel	6 ⁵ /8"
Z22-7 HSS	16"	16	1/16"	Steel	10 ⁵ /8"
Z22-29 HSS	16"	8	1/16"	Steel/Aluminum	10 ⁵ /8"
Z22-33 HSS	16"	6	1/16"	Cast Iron	10 ⁵ /8"
Z22-72 HSS	20"	14	5/64"	Steel	14 ⁵ /8"
Z22-30 HSS	21"	12	1/16"	Steel	15 ⁵ /8"
Z22-30 HSS-SL*	21"	12	1/16"	Stainless Steel	15 ⁵ /8"
Z22-73 HSS	24"	14	5/64"	Steel	181/2"
Z22-74 HSS	24"	8	5/64"	Steel/Aluminum	18 ¹ / ₂ "
Z22-75 HSS	30"	12	5/64"	Steel	24 ⁷ /8"
Z22-75 HSS-SL*	30"	12	5/64"	Stainless Steel	24 ⁷ /8"
Z22-76 HSS	30"	6	5/64"	Cast Iron	24 ⁷ /8"
Z22-37 HSS	37"	12	5/64"	Steel	31 ⁷ /8"

^{*} Use HSS-SL Blades for best cutting performance on stainless steel and hard metal. Blades for plastic, wood and masonry also available.