

Magnetic drilling machine

ECO.60S

Technical data

	Metric	Imperial
Annular cutting	Ø 12 - 60 mm	Ø 1/2" - 2 3/8"
Twist drilling	Ø 1 - 23 mm	Ø 1/16" - 15/16"
Countersinking	Ø 10 - 65 mm	Ø 3/8" - 2 9/16"
Length	320 mm	12 5/8"
Width	200 mm	7 7/8"
Height max.	452 - 622 mm	17 13/16" - 24 1/2"
Stroke	170 mm	6 11/16"
Weight	13 kg	28,7 lbs
Magnet (l x w x h)	168 x 84 x 49 mm	6 5/8" x 3 5/16" x 1 5/16"
Magnetic force	1850 kg	4080 lbs
Motor power	1600 W	14.5 A
Total power	1700 W	15.4 A
Speed (no load)	(I) 60 - 275 rpm (II) 100 - 500 rpm	
Speed (load 1600 W, 14.5 A)	(I) 60 - 275 rpm (II) 100 - 500 rpm	
Spindle (Weldon)	MT3 19,05 mm	MT3 3/4"
Voltage	110 - 120 V / 60 Hz 220 - 240 V / 50 - 60 Hz	



Features:



Adjustable
speed



Overheat
protection



Oil lubricated
gearbox



Magnet
LED-indicator

Benefits:

- High accuracy capstan hub;
- Morse Taper 3 spindle with integrated tool cooling and lubrication;
- Integrated slide and two-speed oil lubricated gearbox for:
 - High accuracy;
 - Enlarged lifecycle;
 - Minimal vibration;
- High precision height adjustment for:
 - Low maintenance;
 - Minimal wear correction;
- Strong dual coil CNC machined magnet.