

Magnetic drill ECO.55



2 3/16"



15/16"



2 3/8"



30



14.5 A



4100



6 11/16"



Soft
start



Overload
protection



Heat
protection



Oil bath
gearbox



Digital
display



LED load
indicators



Smart
restart

The ECO.55 series provide benchmark performance with regards to stability, durability and sheer cutting performance. Coming forth from years of continuous improvement and dedicated development these machines are engineered to provide power in the most efficient way possible. In addition we have added various feed assistants to help you maximise the capabilities, including a first-ever digital readout with indicators.

Technical data

Annular cutters	Ø 7/16" - 23/16"
Twist drills	Ø 1/16" - 15/16"
Countersinking	Ø 23/8"
Length	12 5/8"
Width	8"
Height	19 5/16" - 26"
Stroke	6 11/16"
Weight	30 lbs
Magnet (l x w x h)	6 11/16" x 3 3/8" x 1 7/8"
Magnetic force	4100 lbs
Motor power	14.5 A
Total power	15.5 A
Speed	(I) 60 - 275 rpm
(no load/load)	(II) 100 - 500 rpm
Spindle (Weldon)	MT3 3/4"
Power source	110V/220V 50/60 Hz

Features

- High precision slide & rail construction
- Integrated oil bath gearbox
- Morse Taper 3 Spindle
- External access to auto shut-off carbon brushes
- Digital power read-out display
- Smart Restart technology

