



NOVAX®

Class 3 Rubber Insulating Glove with Contour Cuff - 18"

- Contoured shape reduces hand fatigue
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability
- Contour cuff for increased mobility and comfort on the job
- Silicone free
- Individually numbered for traceability and stamped with factory manufacturing date

Applications

- Power Generation
- Electrical Contractors
- Plant Maintenance
- Utility Work
- Hybrid Automotive Repair, Service and Manufacturing

Technical Data

Color	Black
Sizes Available	8-12
Packaging	Boxed
Packed	6 Pair/Case
Case Dimensions (in)	21.14 x 18.15 x 11.89
Case Weight (lbs)	18.74
Country of Origin	Malaysia
Material	Rubber
Length	18"
Cuff	Contour
Cuff Color	Red
Construction	--
Certifications	NFPA 70E, ASTM D120, Silicone Free
Product Circularity	--

Performance Data

Electrical Class	Class 3
------------------	---------

Care Instructions

Wash in warm water (29°C/85°F) with mild detergent and disinfect with a small amount of chlorine bleach. Air or tumble dry at low heat (74°C/165°F). Gloves may be dusted lightly with talc to reduce tackiness. Gloves should be stored in a glove bag, finger tips up, hung and not laid flat. Leather protecting glove should be removed before storage. Never fold gloves. Store in as dry and cool (35°C/95°F maximum) location as possible, away from sources of ozone and direct sunlight.



SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
162-3-18/8	Black	8	616314807626	10616314807623	20616314807620
162-3-18/8.5	Black	8.5	616314807664	10616314807661	20616314807668
162-3-18/9	Black	9	616314340123	10616314340120	20616314340127
162-3-18/9.5	Black	9.5	616314340161	10616314340168	20616314340165
162-3-18/10	Black	10	616314455896	10616314455893	20616314455890
162-3-18/10.5	Black	10.5	616314340208	10616314340205	20616314340202
162-3-18/11	Black	11	616314455902	10616314455909	20616314455906
162-3-18/11.5	Black	11.5	616314694066	10616314694063	20616314694060
162-3-18/12	Black	12	616314425035	10616314425032	20616314425039