



# SPECIFICATION SHEET

## 280-EV6151S-CH

### EVO® 6151 ASCEND™ CAP STYLE SHORT BRIM SAFETY HELMET

- High-Density Polyethylene (HDPE) shell designed with five raised channels running across the top for strength, and an extended back area for extra protection
- EPS (Expanded Polystyrene) liner helps absorb impact
- 6-Point polyester textile suspension system offers unrivaled comfort without compromising performance
- Unique "3D Adjustment" provides a precise fit using harness depth settings unlike any other hard hat on the US market today
- Revolution™ Wheel Ratchet is easy to use and creates a firm comfortable fit
- Includes a 4-point cross-over chin strap with quick release buckle that is adjustable for a safe & secure fit
- Chamlon sweatband
- Universal accessory slots accepts virtually any helmet
- Packed ready-to-wear with no installation of the suspension required
- Meets ANSI/ISEA Z89.1, Type I requirements
- Vented and Non-Vented, EVOSpec™ compatible
- Added impact benefits as outlined in the EN12492 - Mountaineering Standard

### APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- Energy companies
- High-risk environments where high impact situations are of concern

### CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

### TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene Recyclable Liner: EPS (Expanded Polystyrene) Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating
COLOR	<input type="checkbox"/> White (-10) <input type="checkbox"/> Yellow (-20) <input type="checkbox"/> Black (-11)
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")
BRIM SIZE	Cap
PACKAGING	10 per case
CASE	23.03" x 9.44" x 18.01" / 58.5 cm x 24.0 cm x 45.75 cm
CASE WEIGHT	10.0 lbs / 4.5 kg
COO	USA




### BARCODES

ITEM	EACH	CASE
<input type="checkbox"/> 280-EV6151S-CH-10	5038428367509	5038428367516
<input type="checkbox"/> 280-EV6151S-CH-20	5038428367523	5038428367530
<input type="checkbox"/> 280-EV6151S-CH-11	5038428367547	5038428367554
ITEM	EACH	CASE
VENTED HARD HATS (CLASS C)		
<input type="checkbox"/> 280-EV6151SV-CH-10	5038428367561	5038428367578
<input type="checkbox"/> 280-EV6151SV-CH-20	5038428367585	5038428367592
<input type="checkbox"/> 280-EV6151SV-CH-11	5038428367608	5038428367615

### DIMENSIONS (in)

	EXTERIOR DIM
<b>A</b>	12.5
<b>B</b>	6.38



**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.