

SPECIFICATION SHEET 280-HP341R

DYNAMIC DOM SMOOTH DOME HARD HAT

- Meets -ANSI/ISEA Z89.1 Type 1 and CSA Z94.1 Type 1 requirements
- Fulfills Class E Electrical Insulation requirements
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- SURE LOCK wheel adjustment system for one hand size adjustments
- Precise height adjustment settings to ensure proper depth
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when workers are looking down or bending over
- Non-chaffing, replaceable foam sweatband for maximum sweat absorption
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- · Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Demolition
- Manufacturing
- Energy companies
- Metalworking

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extreme temperatures.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE	
COLOR	□ White (-01) Sky Blue (-07) Red (-15) ■ Yellow (-02) Navy Blue (-08) Royal Blue (-17) ■ Orange (-03) Gray (-09) Steel Blue (-71) ■ Dark Green (-04) Black (-11) Forest Green (-74)	
SIZES	6-8 (52cm-64cm))	
WEIGHT	0.75 lbs / 0.34 kg	
PACKAGING	12 per case	
CASE	17.5" x 12.5" x 24.5" / 44.4cm x 31.75cm x 62.23cm	
CASE WEIGHT	13.1 lbs / 5.95 kg	
C00	Canada	

BARCODES

ITEM	EACH	CASE
☐ 280-HP341R-01	620606001098	10620606001095
280-HP341R-02	620606001104	10620606001101
280-HP341R-03	620606001111	10620606001118
■ 280-HP341R-04	620606001128	10620606001125
280-HP341R-07	620606001159	10620606001156
■ 280-HP341R-08	620606001166	10620606001163
280-HP341R-09	620606001173	10620606001170



■ 280-HP341R-11	620606001197	10620606001194
280-HP341R-15	620606001210	10620606001217
■ 280-HP341R-17	620606001227	10620606001224
■ 280-HP341R-71	620606001234	10620606001231
280-HP341R-74	620606001241	10620606001248

DIMENSIONS (in/cm)

Α	6.5/16.51
В	12.0/30.48

