

SPECIFICATION SHEET 280-HP642R

KILIMANJARO™ TYPE II FULL BRIM HARD HAT

- Meets ANSI Z89.1-2014 Type II Class E requirements
- CSA certified Z94.1 Type II, Class E
- HDPE Shell
- 4-Pt nylon webbing suspension
- Sure-lock ratchet adjustment
- Full brim
- EPS foam liner provides front, rear and lateral protection from impact and penetration
- Compatible with 4 point chin strap 280-HP542C
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- SURE LOCK wheel adjustment system for one hand size adjustments
- Precise height adjustment settings to ensure proper depth
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when workers are looking down or bending over
- \bullet Non-chaffing, replaceable foam sweatband for maximum sweat absorption
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- · Oil & gas
- Mining
- DemolitionManufacturing
- Energy companies
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extreme temperatures.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE Impact Liner: EPS	
COLOR	☐ White (-01)	
SIZES	6-8 (52cm-64cm)	
WEIGHT	1.15 lbs / 0.52 kg	
PACKAGING	12 per case	
CASE	23" x 20" x 26" / 58.42cm x 50.8cm x 66.04cm	
CASE WEIGHT	14.2 lbs / 6.44 kg	
C00	Canada	



BARCODES

ITEM	EACH	CASE
☐ 280-HP642R-01	620606001531	10620606001538
280-HP642R-02	620606001548	10620606001545
280-HP642R-03	620606001555	10620606001552
■ 280-HP642R-04	620606001562	10620606001560
■ 280-HP642R-08	620606001609	10620606001606
■ 280-HP642R-09	620606001616	10620606001613
280-HP642R-15	620606001654	10620606001651

DIMENSIONS (in)

