

SPECIFICATION SHEET

10.25" COTTON LINED POLY TUFF ESD SOLVENT GLOVE

- Superior chemical protection while delivering ESD resistance
- Static dissipative, surface resistance 103 107 ohms
- High grip surface
- 100% cotton knit liner plus conductive fiber for extra comfort
- Excellent resistance to a broad range of solvents
- · Can be used in a temperature range from
- Great abrasion resistance
- ESD safe

APPLICATIONS

- Aerospace
- Automotive
- Chemical
- Construction
- Electronics
- Machinery & Equipment
- Metal Fabrication
- Military
- Oil
- · Gas & Mining

CARE INSTRUCTIONS

Rinse gloves carefully to remove any dirt or liquid. Dry in shade. Do not dry in sun. Store in a well-ventilated place.

TECHNICAL DATA

MATERIAL:	Polyurethane		
LINING:	100% Cotton with conductive fibers		
THICKNESS	6.6 Mil		
COLOR	■ Black		
SIZES	L-XL		
PACKAGING	1 pr		
C00	Japan		

The level of this glove is 0. The Break Through Time is less than 10 minutes.

TABLE OF SURFACE-AREA SWELLING RATIOS

Unit: times (where prior to immersion = 1.0)

Chilt. Limes (where phor to immersion — 1.5)					
TOLUENE	1.6	ISOPROPYL ALCOHOL	1.2		
XYLENE	1.6	TETRAYDROFURAN	3.3		
BENZENE	1.7	ACETONE	1.3		
TRICHLOROETHYLENE	2.0	METHYL ETHYL KETONE	1.6		
DICHLOROMETHANE	2.4	ETHYL ACETATE	1.5		
CHLOROFORM	3.4	DIMETHYLFORMAMIDE	DISSOLVES		



BARCODES

ITEM	PAIR	DOZEN	CASE
■ 300L	616314278181	10616314278188	20616314278185
■ 300XL	616314278211	10616314278218	20616314278215

DIMENSIONS (in/cm)

	L	XL
A	10.25 / 26.04	10.25 / 26.04
В	4.625 / 11.75	5.25 / 13.34

