



**FLANGED HOODS FIT BOTH CHIMED DRUMS & ENVIRONMENTAL PACKS!**


**WWIC-11 REUSABLE DRUM CORE** for all coreless drums. Prevents wire flip.



- ▶ Hood covers designed for 20", 20.4", 23.4", and 26" drums (508, 518, 594 & 660mm)
- ▶ Constructed of tough polyethylene for long shop life
- ▶ Dual windows provide easy access and viewing
- ▶ Flange on hood securely anchors hood to package
- ▶ Orbital Arm or Direct Pull Kit guarantee smooth wire feeding
- ▶ **Lifetime guarantee against breakage**

### DIRECT PULL KIT Model WWDP

- ▶ Quick disconnect with polished ceramic inlet prevents wire shaving
- ▶ Fits all cone and wire sizes
- ▶ **Lifetime guarantee not to wear out**



WWDP SIDE




CERAMIC INLET



ROUND DRUM HOOD



OCTAGON DRUM HOOD



LOW PROFILE OCTAGON HOOD




SQUARE DRUM HOOD



**ORBITAL ARM KITS** Prevents wire from tangling in drum.

- (1) A-4 QD
- (2) WWRL-H3  
WWRL-H4
- (3) C-1H



### WIRE PRESENCE SENSOR BLOCK & PROXIMITY SWITCH

Model WWSB-M12 / WWA5-E34 (OR -E35)

- ▶ Detects & signals when wire drum is empty
- ▶ Proximity switch may be connected to PLC to stop welding cycle when wire is depleted
- ▶ Uses 12 mm proximity switch (WWA5-E34), other switches available upon request
- ▶ Compatible with all Wire Wizard® Drum Hoods

**SEE BACK PAGE FOR MORE INFO & PART NUMBERS**

## ROUND DRUM HOODS 20"-23" (508-584MM) HOODS FIT BOTH CHIMED DRUMS & ENVIRONMENTAL PACKS



DESCRIPTION	PART NO.
20.4" (518mm) Round Hood Only	WW10204F
20.4" (518mm) Round Hood w/Direct Pull Kit	WW10204F-DP
23" (584mm) Round Hood Only	WW10231F
23" (584mm) Round Hood w/Direct Pull Kit	WW10231F-DP
26" (660mm) Round Hood Only	WW10260F
26" (660mm) Round Hood w/Direct Pull Kit	WW10260F-DP
26" (660mm) Round Hood, for chimed drums only	WW10260C-2
26" (660mm) Round Hood w/Direct Pull Kit, for chimed drums only	WW10260DP-2

## OCTAGON DRUM HOODS



20.5" (521mm) Octagon Hood (500 LB / 227 KG)	WWOC-20.5
20.5" (521mm) Octagon Hood w/Dir. Pull Kit	WWOC20.5-DP
23.5" (597mm) Octagon Hood (900 LB / 408 KG)	WWOC-23.5
23.5" (597mm) Octagon Hood w/Dir. Pull Kit	WWOC23.5-DP
23.5" (597mm) Low Profile Hood (900 LB / 408 KG)	WWOC
23.5" (597mm) Low Profile Hood w/Dir. Pull Kit	WWOC-DP

## SQUARE DRUM HOODS



21" (533mm) Square Hood (500 LB / 227 KG)	WWSC-21
21" (533mm) Square Hood w/Direct Pull Kit	WWSC21-DP
24" (610mm) Square Hood (1000 LB / 453 KG)	WWSC-24
24" (610mm) Square Hood w/Direct Pull Kit	WWSC24-DP
29" (737mm) Square Hood (990 LB / 449 KG)	WWSC-29

## DODECAGON HOODS & ACCESSORIES

For 100 lb (45.4 kg) & 300 lb (136 kg) aluminum wire packages



DESCRIPTION	PART NO.
23.5" (597mm) Dodecagon Hood	WWDO-23.5
Connector for EC-4 Conduit	A-12A

## ADDITIONAL EQUIPMENT

DESCRIPTION	PART NO.
Direct Pull Kit	WWDP
Sensor Block (12mm)	WWSB-M12
Proximity Switch (PNP)	WWA5-E34
Proximity Switch (NPN)	WWA5-E35
Reusable Drum Core	WWIC-11
Conduit Connection Insulator	WWDI

## ORBITAL ARM KITS (with Quick Disconnect)

### COMPATIBLE DRUM COVERS & WIRE



DESCRIPTION	PART NO.
20" (508mm) to 23.4" (594mm) Cover for up to .062 (1.6mm) Wire	WWOA-20
20" (508mm) to 23.4" (594mm) Cover for .062-3/32 (1.6-2.4mm) Wire	WWOA-20H
20" (508mm) to 23.4" (594mm) Cover for .062-3/32 (1.6-2.4mm) Alum.	WWOA-20A
26" Drum Cover for Wire Diameter up to .045	WWOA-26

### AVAILABLE ORBITAL ARM REPLACEMENT PARTS

(1) Quick Disconnect (QD)	A-4
(2) Replacement Liner for WWOA-20 and WWOA-26	WWRL-H3
Replacement Liner with Inlet Guide for WWOA-20H	WWRL-H4
(3) Inlet Guide with Ceramic Insert	C-1H